

# YOUR TYRE CHANGER OF CHOICE

T7700 provides a superior set of tools to minimize effort and the damaging risks when working with run-flat and high performance tyres

INTRODUCING THE T7700

PROFESSIONAL TYRE CHANGER



## HIGH PRODUCTIVITY

## **EASE OF USE LESS TECHNICIAN'S FATIGUE**

## KFY FFATURES

### **POWERMONT™**

### The innovative system to mount & demount tyres

- SAFE: Thin mount / demount finger protects the bead from stress during mounting - Servo assisted movement of the mount /demount tool, the finger follows the rim profile and prevents damages of TPMS and valve - Integral and soft tool protection avoids rim damage
- FAST: Automatic synchronization of all tools positions - Fast disengage and repositioning of the mount demount tool
  - Standalone tool for lower bead mounting
- EASY TO USE: Control of the mount/demount tool's trajectory - Intuitive and simple control of the operations
- **RELIABLE**: Long lasting mount / demount tool made of steel with integrated plastic protection

## DYNAMIC BEAD BREAKER

### The bead breaking of choice for RFT, UHP and low aspect ratio tyres

- Precise and damage free
- Disk position synchronized by servo drive Fast & precise
- Disk pneumatic tilt Optimum performance with sticked beads
- Ergonomic & effortless

## CENTER POST CLAMP

### The solution choice for light alloy wheels

- No wheel damage
- Does not require jaw protection
- Not restricted by clamping jaw maximum opening
- Faster clamping of UHP and RFT, it does not require use of the bead assist device to insert the jaws between the bead and the rim

PROspeed<sup>™</sup> continuously controls the mount/ demount conditions in order to provide the optimum torque/speed combination to the motor



- **SAFE**: always the most appropriate torque to avoid interruption of the process and damages to tyre and rim
- FAST: automatically selects the maximum speed possible up to 20 rpm
- EASY TO USE: PROspeed™ automatically sets the speed to the torque required

## PNEUMATIC BEAD DEPRESSOR PBD330

### The essential tool working with high performance tyres

- PBD330 keeps tyre bead into the wheel drop center for a safe and correct mounting / demounting of tyres with stiff sidewall
- The tool shape is optimized to avoid tool slippage that could damage tyres and wheels
- Tool's rear hook helps lifting heavy tyres

Features	T7700b	T7700g
Clamping range	12" - 30"	12" - 30"
Max tyre width	380 mm	380 mm
Max wheel dimension	47"	47"
PROspeed™	CW 7 - 20 rpm	CW 7 - 20 rpm
powerMONT™	standard	standard
Bead seater	n.a	standard
Bottom bead viewer	mirror	camera
Wheel lift & Tools storage	option	option

Snap-on Equipment s.r.l. · Via Prov. Carpi, 33 · 42015 Correggio (RE) Phone: +39 0522 733-411 · Fax: +39 0522 733-479 · www.johnbean.com

Snap-on Equipment France  $\cdot$  ZA du Vert Galant  $\cdot$  15, rue de la Guivernone BP 97175 - Saint-Ouen-l'Aumône · 95056 Cergy-Pontoise CEDEX Phone: +33 134 48 58-78 · Fax: +33 134 48 58-70 · www.johnbean.com

Snap-on Equipment GmbH · Konrad-Zuse-Straße 1 · 84579 Unterneukirchen Phone: +49 8634 622-0 · Fax: +49 8634 5501 · www.johnbean.com

Snap-on Equipment s.r.l. · Via Prov. Carpi, 33 · 42015 Correggio (RE) Phone: +39 0522 733-411 · Fax: +39 0522 733-410 · www.johnbean.com

Snap-on Equipment Ltd. · Unit 17 Denney Road, King's Lynn · Norfolk PE30 4HG Phone: +44 118 929-6811 · Fax: +44 118 966-4369 · www.johnbean.com

Part of the machines is illustrated with optional extras which are available at extra cost. Technical modifications reserved.

Cod.: 1809 501 · 10/2018